

FSG Refrigerant, Type KM 1 PLUS

Intended Use

- For spraying on the edges of the furniture part after applying the plastic or veneer edge

Characteristics

- The applied Refrigerant discharge the edge band statically and cools the glued joint at the same time
- Follower roll and work piece stay free from millings
- Glue cure faster

Instructions for Use

- Fill the containers of the spraying system with the Refrigerant and set the optimum spray intensity.
- For safety reasons, check the selected settings at the first workpieces.
 - Glue residues do not adhere?
 - More detergent is sprayed as necessary?
- If necessary, adjust the setting of spray intensity.

Technical Data and Shelf Life

Condition of aggregation:	liquid
Colour:	bluish
Odour:	Alcohol-/Paraffin smell
Shelf Life:	2 – 3 Years

Safety Precautions

- Highly flammable liquid and vapour.
- Causes serious eye irritation.
- Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Ground and bond container and receiving equipment.
- Take action to prevent static discharges.
- Wear protective gloves/protective clothing/eye protection/face protection.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- If eye irritation persists: Get medical advice/attention.

Extract from the legal texts. More details on the label and safety data sheet.

Disposal

- Do not allow to enter into surface water or drains.
- Return empty containers to manufacturer or emptied and degassed for material recycling options.
- Dispose of waste according to applicable legislation.
- Dispose residues of the cleaner corresponding waste code 14 06 03 (other solvents and solvent mixtures).
- For more information see safety data sheet or consult the appropriate local waste disposal expert.

Packaging

500 ml	Plastic bottle
1.000 ml	Plastic bottle
1.000 ml	Plastic bottle with spray nozzle
5 lt	Plastic canister
10 lt	Plastic canister
30 lt	Plastic canister
30 lt	Steel can
200 lt	Steel barrel
1.000 lt	IBC

This information has been carefully checked, should not and cannot be legally binding and do not exempt you from own tests of the products supplied by us as to their suitability for the intended applications. Optionally, methods need to be adapted to the specific requirements in each case.